




Demand more. Choose Foster

FPS4HR Refrigerated Prep Counter

FPS4HR



Temperature



Refrigerator 1/4 °C

Dimensions (mm)

| | | |
|--------|--------|-------|
| | W 2302 | D 850 |
| H 1059 | | |

Capacity

570 Litres

Unpacked Weight

308 KG

Features & Benefits

Foster's Prep Station range offers a universal solution to the key area of food preparation of pizzas, sandwiches, salads, starters, desserts, or ethnic dishes

- High Quality 304 Stainless Steel Exterior Build Quality
- All pans and the worktop are within comfortable reach - an important health and safety benefit
- The inner catch-tray in the pan section prevents food from falling into the storage area
- Efficient Refrigeration - Already best in class, new airflow design has further improved performance
- Rear mounted refrigeration maximises storage space and makes it easily accessible for servicing

| External Finish | |
|--|----------------------|
| 304 Stainless Steel | Standard |
| 304 Stainless Steel Rear For Island Siting | Option |
| Internal Finish | |
| 304 Stainless Steel | Option |
| Aluminium | Standard |
| Shelving | |
| Additional Shelf | Option |
| Nylon Coated Shelf | Quantity: 8 Standard |
| Gastronorm 1/3 Pans (Not Supplied) | Option |
| Base Fittings | |
| 80mm Castors | Standard |

| Doors | |
|---------------------------|----------|
| Solid Full | Standard |
| Worktop & Drawers | |
| Temperature | |
| Worktop | Standard |
| Night Cover for Saladette | Option |
| Cutout | |
| Granite Worktop | Option |
| Sauce Container Recess | Option |
| Drawers | Option |
| Refrigeration | |
| Forced Air | Standard |
| Integral | Standard |
| R134a | Standard |
| Drain Required? | No |

| Electrical Data & Service Information | |
|---------------------------------------|----------|
| 230 Volts | Standard |
| 50Hz | Standard |
| 1 Phase | Standard |
| Running Watts | 1147 |
| Running Amps | 6.2 |
| Thermal Heat Rejection (W) | 1,279 |
| Noise (dBa @ 1m) | 69.4 |
| Fuse Required (A) | 10 amp |
| Product Extras | |
| Helicoil Mains Lead | Option |

Footnotes

- Pan Storage Temperature +3/+5oC
- Pan Holders take pans up to a maximum 150mm depth
- Gastronorm pans are not supplied as standard with Prep Station - please order separately
- Decibel rating measured 1m high from the floor and 1m from the cabinet

Foster-Fridge.com

Telephone: **01582 865050** Facsimile: **01582 645947** Email: info@foster-fridge.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster