

Product Code: FS90 27-108

Air cooled standard Ice Cuber



Features & Benefits

- · Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- Uses as little as 5 litres of water to produce 1 kilo of ice important where water is metered.
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Legs provided as standard to increase height for drainage where required 70mm maximum height increase
- Bin capacity: 89kgs
- Ice: Cubed 35x37x32mm

| External Finish | | Internal Finish | | Refrigeration | |
|---|----------|-----------------------|----------|-------------------------------|----------|
| Stainless steel | Standard | N/A | Standard | R134a - Industry Standard | Standard |
| Electrical, Service & Ecodesign Data | | Specification | | Drain Rqd | 20mm |
| | | | | Integral | Standard |
| | | Dimensions (Width) | 700 | Integral Refrigeration System | Standard |
| 230/50/1 | Standard | Dimensions (Height) | 995 | | |
| Fuse Required | 13 | Dimensions (Depth) | 580 | | |
| | | Cube - 31 x 24 x 26mm | Standard | | |
| | | Noise Dba @ 1M | TBC | | |
| | | 83 | Standard | | |

Footnotes

- Output figures quoted are based on 10°C water input and ambient air temp of 21°C
- Dimensions: Legs provided as standard to increase height for drainage where required 180cm maximum height increase
- Note: A minimum clearance of 15cm (6") must be left at the sides of the machine for routing cooling air drawn into and exhausted out of the compartment to maintain a proper condensing operation



Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU Phone 08432 168800 | Email sales@foster-uk.com | Visit www.fosterrefrigerator.com