




Demand more. Choose Foster

EcoPro G2 600 Litre Upright Dual Temperature Refrigerated Cabinet

EP700HL



Temperature

 Dual +1/+4 °C

Dimensions (mm)

W 700 D 865

H 2080



Capacity

600 Litres

Unpacked Weight

155 KG

Features & Benefits

We've revolutionised professional refrigeration... again. Built from the ground up to include over 50 new features and innovations, the EcoPro G2 is loaded with new design, quality, reliability efficiency and performance features.

- Dual temperature option offers refrigerator and freezer temperatures in the same cabinet perfect when space is at a premium
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circularair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet

External Finish	
304 Stainless Steel	Option
Stainless Steel	Standard
304 Stainless Steel Rear For Island Siting	Option

Internal Finish	
304 Stainless Steel	Option
Aluminium	Standard

Base Fittings	
80mm Castors	Standard
150mm Legs	Option

Doors	
Solid Half	Standard
Hinged - Right Hand	Standard
Hinged - Left Hand	Option

Refrigeration	
Forced Air	Standard
Integral	Standard
R404a	Standard
R134a	Standard
Drain Required?	No

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
60Hz	Option
1 Phase	Standard
Running Watts	744
Running Amps	4.1
Thermal Heat Rejection (W)	754
Noise (dBa @ 1m)	TBC
Fuse Required (A)	10 amp

Footnotes

- Marine kit option includes legs, bulkhead brackets & marine shelves.
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm.
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet.

Foster-Fridge.com

Telephone: **01582 865050** Facsimile: **01582 645947** Email: info@foster-fridge.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster