


## Foster Slim 1200 Multideck with Nightblind and Glass FMSLIM1200NG



## Temperature



| Unpacked Weight |  |  |  |  |  |
|-----------------|--|--|--|--|--|
| 190 KG          |  |  |  |  |  |

## Features & Benefits

The Foster Slimline is a stylish, flexible and economical option for outlets where space is at a premium. Easy to clean and maintain, this range is admired for its low noise levels, all of which makes it ideal for the smaller display area. Key to the range is the oversized display volume, courtesy of its extra-large, flexible and versatile shelf depths.

- 2x vertical side mounted full length LED lights. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Energy saving retracting 'Soft Closing Mechanism' Nightblind.
- Fully removable shelves and supports for ease of cleaning.
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

| External Finish                         |          | Refrigeration                |                                | Electrical Data & Service |          |
|---|----------|------------------------------|--------------------------------|---------------------------|----------|
| 304 Stainless Steel                     | Standard | Integral                     | Standard                       | Information               |          |
|   |          | Depth                        | Please allow an additional     | 230 Volts                 | Standard |
| Internal Finish                         |          | Note:                        | 60mm to the depth of the       | 50Hz                      | Standard |
| 304 Stainless Steel Standard            |          | product as spacers are       | 1 Phase                        | Standard                  |          |
|   |          | required for air circulation | Running Watts                  | 1406                      |          |
| Shelving                                |          |                              | (fitted as standard). The unit |                           | 1400     |
|   |          |                              | is designed to operate         | Running Amps              | 5.8      |
| Shelves Quantity: 4 Standard (Including |          |                              | between +2/+4°c, in EN441      | Thermal Heat Rejection    | 1,472    |
|   |          |                              | Climate Class 3 25°            | (W)                       |          |
| Base as                                 |          |                              | ambient 60% RH.                | Noise (dBa @ 1m)          | TBC      |
| shelf)                                  |          | R404a                        | Standard                       | Fuse Required (A)         | 10 amp   |
| Base Fittings                           |          |                              |                                |                           |          |
|   |          |                              |                                |                           |          |

Footnotes

High Quality Rollers

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wallsited.
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced see UK price list for conditions.

## Foster-Fridge.com

Telephone: 01582 865050 Facsimile: 01582 645947 Email: info@foster-fridge.com





Standard











FULL SCOPE LOW PRODUCT MILES ISO 14001

Demand more. Choose Foster