

Body/Shell



ECO PRO
G2



xtra BY FOSTER

Capacity



Higher 600 litre capacity:
more fridge for your money



570 litre capacity

Insulation




High performance cyclopentane
foam - more thermally efficient
& maintains insulation
performance longer



Zero ODP, low GWP foam (non
Cyclopentane)





Ref system/
performance



ECO PRO
G2



xtra BY FOSTER



1.5Kw/24hrs – costs less to run
than a traditional lightbulb

EEI = 6.2 – best in class energy
consumption by literage



3.0Kw/24hrs

Energy

Air Distribution



Full length and CFD designed rear
airduct delivers consistent
temperature - Protects food &
reduces energy consumption



Industry standard airflow design
& minimal airduct





System Controls



ECO PRO G2



xtra BY FOSTER



'Smartphone style' touch sensitive hidden-until-lit control panel

Enlarged high visibility bright white PMVA display



Fuzzy logic II intelligent temperature control system for maximum efficiency



Industry standard controller

Standard LED display



Industry standard basic temperature control

Controller





Product Life Cycle



ECO PRO
G2



xtra BY FOSTER

Longevity



Built to last twice as long as conventional products



Robust build quality

Payback



2-2.5 years (standard usage)



No payback





Other Features



ECO PRO
G2




xtra BY FOSTER

Racking



New racking system: added stability

Anti-tilt trayslides: ease of loading/unloading



Conventional racking set up

Standard trayslides

Door



Self closing doors and high impact door hinges

Tested on 300,00 door openings



Standard hinges

