Gamko E3/222GMU84

Eco-Line Noverta Premium I Plug ready bottle under counter cooling cabinets







Temperature



+4°C / +8°C

Dimensions (mm) W x D x H



1988 x 492 x 840-860/880

Capacity



x 531



x 3

Weight



Net: 106kg - Gross: 124kg

> Electric



Power: 228 Watt Voltage: 220-240V/50Hz~









The E3/222GMU84 Noverta Premium cabinet has a large storage capacity and a superb cooling performance. Highly extra efficient three door bottle cooling cabinet with glass fronts and anthracite frame. Silver grey coated skin plate is used for the interior of the cabinet. Refrigerant: R600a. Standard features are: digital electronic thermostat, automatic defrost, exchangeable magnetic gaskets and two wire mesh shelves per door section, mechanical locks and LED lighting.

• Temperature: +4°C to +8°C

Adjustable temperature range from +2°C to +18°C

• Cooling capacity: 515 Watt

• Power consumption: 228 Watt

· Refrigerant: R600a

Illumination: LED light strips

Digital electronic thermostat

Locks





Gamko E3/222GMUCS84

Eco-Line Noverta Premium I Plug ready bottle under counter cooling cabinets







Temperature



> Dimensions (mm) W x D x H



1988 x 492 x 840-860/880

Capacity



x 531



x 3

> Specifications

The E3/222GMUCS84 Noverta Premium cabinet has a large storage capacity and a superb cooling performance. Highly extra efficient three door bottle cooling cabinet with glass fronts and stainless steel frame. Silver grey coated skin plate is used for the interior of the cabinet. Refrigerant: R600a. Standard features are: digital electronic thermostat, automatic defrost, exchangeable magnetic gaskets and two wire mesh shelves per door section, mechanical locks and LED lighting.

- Temperature: +4°C to +8°C
- Adjustable temperature range from +2°C to +18°C
- Cooling capacity: 515 Watt
- Power consumption: 228 Watt
- Refrigerant: R600a
- · Stainless steel exterior
- Illumination: LED light strips
- Digital electronic thermostat
- Locks

Weight



Net: 106kg - Gross: 124kg

Electric



Power: 228 Watt Voltage: 220-240V/50Hz~











