



Product Code: EP1/2H 12-170

EcoPro G2 1/2 Refrigerated Counter with Saladette Cut Out



Features & Benefits

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Saladette dimensions 510 x 305mm
- Accepts 1 x GN1/1 pan or 3 x GN1/3 pans per saladette

Shelving

Gastronorm Pans	Option
Additional S/S Trayslides	Option
Additional GN1/1 Shelf	Option

Refrigeration

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
RH Mounted Ref Unit	Option

Specification

Refrigerator +1/+4°C	Standard
Width (mm)	1415
Depth (mm)	700
Height (mm)	865
Unpacked weight (Kgs)	123
Packed weight (Kgs)	139.91
Gross Volume (Ltr)	280
Noise dBA @ 1m	65.2

Base Fittings

Remote Refrigeration System	Option
Castors 80mm	Standard
100mm legs in lieu of castors	Option
Legs 150mm	Option

Electrical & Service Data

Connect Load	275
230/50/1	Standard
Fuse Required (A)	10
Refrigerant Charge (kg)	0.150

Finish

304 s/s	Standard
304 S/S back for island sitting	Option
Worktop	Standard

Doors

Left and right hinged door	Option
Solid	Standard

Product Extras

Helicoil Mains Lead	Option
---------------------	--------

Energy

AEC	394.83
Nett Volume	172.3
Energy Grade	A
Global Warming Potential	3
Energy Efficiency Index	17.70

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.