

Product Code: EP700H2 10-143 EcoPro G2 600 Litre Upright Half Door Refrigerated Cabinet



Features & Benefits

- The half door option is designed to save energy by preventing old air loss during regular use in a hot kitchen
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Keep accessible products in the top section, bottom half can remain shut for longer preventing cold air loss.


Shelving		Base Fittings		Doors	
Additional S/S Trayslides	Option	Castors 80mm	Standard	Half	Standard
Additional GN2/1 Shelf	Option	Legs 150mm	Option	Left Hand Hinged Door	Option
Refrigeration		Electrical & Service Data		Product Extras	
R290 - Energy Efficient	Standard	Connect Load	349	Helicoil Mains Lead	Option
Integral Refrigeration System	Standard	230/50/1	Standard	Energy	
Less Condensing Unit	Option	220/60/1 Electrical Supply	Option	, , , , , , , , , , , , , , , , , , ,	
Specification		Fuse Required (A)	10	kWh (24 hours)	1.37
		Refrigerant Charge (kg)	0.110	AEC	499.9803398
Refrigerator +1/+4°C	Standard			Nett Volume	482.3
Width (mm)	700	Finish		Energy Grade	C
Depth (mm)	820	304 s/s	Standard	Global Warming Potential	3
Height (mm)	2080	304 S/S back for island sitting	Option	Energy Efficiency Index	35.68
Unpacked weight (Kgs)	121				
Packed weight (Kgs)	132.6				
Gross Volume (Ltr)	600				

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet

Energy Performance Data and information







Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies













Quality Value

Hygiene

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.