

Product Code: EP700L2 10-147

EcoPro G2 600 Litre Upright Half Door Freezer Cabinet



Features & Benefits

- The half door option is designed to save energy by preventing old air loss during regular use in a hot kitchen
- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Keep accessible products in the top section, bottom half can remain shut for longer preventing cold air loss.

Shelving		Base Fittings		Doors
Additional S/S Trayslides	Option	Castors 80mm	Standard	Half
Additional GN2/1 Shelf	Option	Legs 150mm	Option	Left Hand Hinged Door
Refrigeration		Electrical & Service [Data	Product Extras
R290 - Energy Efficient	Standard	Connect Load	675	Helicoil Mains Lead
ntegral Refrigeration System	Standard	230/50/1	Standard	Energy
ess Condensing Unit	Option	220/60/1 Electrical Supply	Option	Litergy
Specification		Fuse Required (A)	10	kWh (24 hours)
Specification		Refrigerant Charge (kg)	0.120	AEC
reezer -18/-21°C	Standard			Nett Volume
Width (mm)	700	Finish		Energy Grade
Depth (mm)	820	304 s/s	Standard	Global Warming Potential
leight (mm)	2080	304 S/S back for island sitting	Option	Energy Efficiency Index
Jnpacked weight (Kgs)	121			
Packed weight (Kgs)	132.6			
Gross Volume (Ltr)	600			

Standard

Option

Option

4.87

D

3

50.84

1778.134

410.9885

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet

Energy Performance Data and information



Coster Refrigerator- a division of ITW Ltd Oldmedow Road, KINO'S LYNN, Norfolk PE30 4UU Registered in France



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies



All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.