



Product Code: EP700W 10-159

G2 600 Litre Upright Glass Door Wine Cabinet



Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Glass door cabinet for easy visibility of stored product, operates up to 32 degrees
- Energy efficiency LED lighting for clear display
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

Shelving

Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

Refrigeration

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
Less Condensing Unit	Option

Specification

Wine +10/+12°C	Standard
Width (mm)	700
Depth (mm)	820
Height (mm)	2080
Unpacked weight (Kgs)	121
Packed weight (Kgs)	132.6
Gross Volume (Ltr)	600
Noise dBA @ 1m	64.9

Base Fittings

Remote Refrigeration System	Option
Castors 80mm	Standard
Legs 150mm	Option

Electrical & Service Data

Connect Load	349
230/50/1	Standard
220/60/1 Electrical Supply	Option
Fuse Required (A)	10

Finish

304 s/s	Standard
304 S/S back for island sitting	Option

Doors

Glass	Standard
Left Hand Hinged Door	Option

Product Extras

Helicoil Mains Lead	Option
----------------------------	--------

Footnotes

- 32°C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.