



Product Code: FMSLIM1200NG 18-105

1200mm Slimline multideck with nightblind and glass end panels



Features & Benefits

- Optimum storage and display from the smallest possible footprint
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (400mm) delivers increased volume compared to competitor slimline cabinets
- Extra wide glass end panels increase display visibility
- Add 60mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Energy saving retracting 'Soft Closing Mechanism' Nightblind.
- Fully removable shelves and supports for ease of cleaning.
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

Refrigeration

R134a - Industry Standard	Standard
Integral Refrigeration System	Standard

Specification

M2 Temp +2/+4°C	Standard
Width (mm)	1195
Depth (mm)	680
Height (mm)	1780
Unpacked weight (Kgs)	190
Packed weight (Kgs)	211.14

Electrical & Service Data

Connect Load	1400
230/50/1	Standard
Fuse Required (A)	10

Finish

304 s/s	Standard
----------------	----------

Product Extras

Additional S/S shelf and support brackets	Option
Front wire baskets for additional storage	Option

Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.



Energy



Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.