



FlexDrawer

Versatile | Cost Effective | Ergonomic

An innovative extension to our counter range, the Foster FlexDrawer allows you to change drawer temperature from fridge to freezer at the touch of a button - simple!



Quick fact:

> FFC3-1 designed to accommodate hot cooking equipment such as broilers, griddles and induction hobs, allowing easy access to food at the point of cooking



Quick fact:

> Drawer runners can hold up to 200kg offering unrivalled drawer performance as standard







> Space saving 775mm width models available, allowing a FlexDrawer to fit into the narrowest of spaces



Image: FFC6-2

Specs

| |  FFC6-2 |  FFC4-2 |  FFC3-1 |  FFC2-1 |
|-----------------------------------|--|--|--|--|
| External Dimensions (wxdxh) mm | 1100 x 700* x 900mm | 775 x 700* x 900mm | 1100 x 700* x 600mm | 775 x 700* x 600mm |
| Refrigerator/Freezer Drawer Temps | +1/+4°C, -18/-21°C | +1/+4°C, -18/-21°C | +1/+4°C, -18/-21°C | +1/+4°C, -18/-21°C |
| Finish | 304 s/s int/ext | 304 s/s int/ext | 304 s/s int/ext | 304 s/s int/ext |
| No. of Drawers | 2 | 2 | 1 | 1 |
| GN1/1 Pan Capacity (not supplied) | 6 (150mm deep) | 4 (150mm deep) | 3 (150mm deep) | 2 (150mm deep) |
| Splashback | Option | Option | Option | Option |
| 304 s/s back | Option | Option | - | - |
| Reduced height option | Available | Available | Available | Available |
| Refrigerant | R290 | R290 | R290 | R290 |
| Power Supply (230/50/1) | Two 10 Amp Plugs | Two 10 Amp Plugs | One 10 Amp Plug | One 10 Amp Plug |
| Hot Gas Defrost | Automatic | Automatic | Automatic | Automatic |
| Castors | Standard | Standard | Standard | Standard |

*Add 20mm to depth if product is to be wall sited (stopper required for air circulation - detachable if not wall-sited).