

Demand more. Choose Foster

BCT52-26 Blast Chiller Cabinet BCT52-26



Temperature



Dimensions (mm)

W 755 D 690

H 1790

Capacity

52 Chilling (Kg)26 Freezing (Kg)

Unpacked Weight

158 KG

Features & Benefits

The Foster tray loading blast chiller range provides the ideal way to ensure quality and food safety is maximised in every kitchen, large or small

- Dedicated 52Kg blast chiller with occasional 26Kg freeze capacity
- Exceeding UK and European food safety requirements
- High grade 304 exterior & interior the 'gold standard' in performance finishes
- Intuitive touch control panel just press and go!

•	A range of intelligent chilling & freezin	g programmes to er	nsure foods are chil	led safely and that q	uality is maintained

External Finish					
304 Stainless Steel	Standard				
Internal Finish	nternal Finish				
304 Stainless Steel	Standard				
Shelving					
Additional Shelf	Option				
Nylon Coated Gastronorm 1/1 Shelf	Option				
Stainless Steel Gastronorm 1/1 Shelf	Option				
Bakery Tray - 60x40	Option				
Base Fittings					
80mm Castors	Standard				
Legs	Option				

Doors			
Solid Full	Standard		
Hinged - Right Hand	Standard		
Hinged - Left Hand	Option		
Refrigeration			
Integral	Standard		
Remote - less condensing unit	Option		
R404a	Standard		
Drain Required?	No		

Electrical Data & Service nformation					
400 Volts	Standard				
50Hz	Standard				
60Hz	Option				
1 Phase	Standard				
Thermal Heat Rejection (W)	2,914				
Noise (dBa @ 1m)	TBC				
Fuse Required (A)	16 amp				
Product Extras					
Door Pull Handle	Standard				
Hold Facility	Standard				
Temperature Probe	Standard				

Hardwired Logging System

Interface

Footnotes

- Chilling Capacity: 52 KG. Freezing capacity: 26KG. 70oC to 3oC in less than 90 minutes within specifications, entry temperature up to 90oC for chilling.
- *Please add 55mm to depth for spacer

Foster-Fridge.com

Telephone: 01582 865050 Facsimile: 01582 645947 Email: info@foster-fridge.com















Option

V

FULL SCOPE ISO 14001

Demand more. Choose Foster