




Demand more. Choose Foster

Foster Display Chiller 900mm Open Front Self Service FDC900



Temperature

 Refrigerator 1/4 °C

Dimensions (mm)

W 900 D 785
H 1435

Capacity

115 Litres

Unpacked Weight

Features & Benefits

If you want best in class British made self-service display, Foster Display Chillers are for you, giving your customers every opportunity to buy on impulse without losing produce quality. The open fronted range is perfect for the storage and display of pre-packaged products such as drinks, sandwiches, sushi and dairy produce.

- ACT (Anti Condensation Technology) helps glass to remain clear, maximising product display
- Glass end panels over 70% wider than many models in the market, maximising your display window
- Thick toughened glass for enhanced safety across both open and closed fronted models
- Manufactured using superior 304 stainless steel – the 'gold standard' in performance finishes meaning quality is assured
- Foster's innovative air curtain protects your merchandise from warmer air entering the display ensuring your food keeps both its taste and texture
- Brilliantly bright LED lighting in top canopy and on every shelf significantly enhances product display
- Innovative design means the controller can be positioned to the front or rear – allowing on site flexibility
- There when you need us: Unrivalled 2 year parts and labour warranty as standard for complete peace of mind (UK only)

External Finish	
304 Stainless Steel	Standard
Internal Finish	
304 Stainless Steel	Standard
Shelving	
10mm Thick Glass Shelving	Quantity: 3 Standard
Base Fittings	
Roller Castors	Standard

Refrigeration	
Forced Air	Standard
Integral	Standard
Depth Note:	Please allow an additional 80mm to the depth of the product as spacers are required for air circulation (fitted as standard). The unit is designed to operate at M2 temperature requirements (EN441 Climate Class 3 25° ambient)
R404a	Standard

Electrical Data & Service Information	
230 Volts	Standard
50Hz	Standard
1 Phase	Standard
Fuse Required (A)	10 amp

Footnotes

- Add 80mm to depth for spacers if product is to be wall-sited (required for air circulation - detachable if not wall-sited)

Foster-Fridge.com

Telephone: **01582 865050** Facsimile: **01582 645947** Email: info@foster-fridge.com

**FOSTER
GREEN
PROCUREMENT**



Demand more. Choose Foster