

Product Code: HR150 3D

Refrigerated Undercounter Cabinet with Drawers



Features & Benefits

- Front breathing refrigeration system, suitable for use even in enclosed areas
- Easy to use microprocessor control with digital display on the front for easy visual reference
- · Stainless steel exterior as standard with aluminium interior
- · Roller castors to rear for ease of movement
- High quality magnetic door gasket
- Operate to ISO Climate class 4 up to 32°C ambient
- Three easy to use drawers give simple access to inventory

Base Fittings		Doors		Refrigeration	
Castors - Rear Fixed	Standard	Solid	Standard	нс	Stan
Levelling Bolts	Standard	Specificatio	n	R134a - Industry Standard	Ol
Electrical & Service	e Data	Refrigerator +3/+5°C	Standard	Integral Refrigeration System	Stan
230/50/1	Standard	Width (mm)	605	Finish	
Fuse Required (A)	10	Depth (mm)	640	s/s ext & alu int	Stan
Refrigerant Charge (kg)	0.065	Height (mm)	830		
Energy		Gross Volume (Ltr)	150		
kWh (24 hours)	0.82	Noise dBA @ 1m	68.8		
AEC	320.29				
Nett Volume	45.7				
Energy Grade	Α				
Global Warming Potential	3				
Energy Efficiency Index	16.80				

Footnotes

- External cabinet depth excludes 25mm door handle
- Note: for ventilation, ensure that 50mm clearance is allowed above and around the cabinet
- Decibel rating measured 1m high from the floor and 1m from the cabinet

Energy Performance Data and information



Foster Refrigerator- a division of ITW Ltd Oldmedow Road, KING'S LYNN, Norfolk PE30 4JU Tel: 0843 216 8800 Fax: 0843 216 4700 Registered in England No. 00559693 VAT No. GB 792 4414 16



Master data version: Ver.01.0007/

Generated: 21/06/2017

Application

This appliance is intended for use in ambient temperatures up to {1}°C **Safety**

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies