

Product Code: EP1/4MFour door meat temp counter



The versatile Foster EcoPro G3 counter range offers a huge selection of models, build options and accessories to ensure you find the perfect storage solution for your business.

Features & Benefits

- A reduced footprint the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel meaning the heaviest usage touchpoints on the product are covered
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Operates efficiently in ambient temperatures of up to 43°C

Shelving		
8 shelves (GN 1/1)	Standard	
Additional S/S Trayslides	Option	
Additional GN1/1 Shelf	Option	
Refrigeration		
R290 - Energy Efficient	Standard	
Integral Refrigeration System	Standard	
Remote Refrigeration System	Option	
Less Condensing Unit	Option	
RH Mounted Ref Unit	Option	
Specification		
Gross volume (Itrs)	585	
Meat -2/+2°C	Standard	
Width (mm)	2270	

base rittings		
Castors 80mm	Standard	
100mm legs in lieu of castors	Option	
Legs 150mm	Option	
Electrical & Service Data		
230/50/1	Standard	
Finish		
304 s/s ext & alu int	Standard	
304 s/s ext & int	Option	

304 S/S back for island sitting

Rase Fittings

Solid		Standard
	Product Extras	
Helicoil	Mains Lead	Option
Splashb	ack	Option
304 S/S I	Back and Unit Cover	Option
	Energy	
Nett Vol	ume	344.5

3

Global Warming Potential

Option

Doors

Footnotes

Depth (mm)

Height (mm)

Worktop

• Castors not available if product supplied less condensing unit

700

865

Standard

- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.