



The Refrigeration Experts

Product specification



EP1440G: 1350 Ltr Cabinet Refrigerator

41-494

- ✓ Robust, high quality glass door
- ✓ Fitted with bright, energy saving LEDs
- ✓ Double door professional fridge
- ✓ Featuring energy saving technology

Why choose this product

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer – all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- This glass door model uses energy efficient LED lighting to enhance the display of stored products
- Market leading usable capacity, now supplied with 8 shelves as standard making your money go further – holds more than a conventional fridge

Specification

Technical

Temperature	Refrigerator +1/+4°C
Thermal heat rejection (W)	245
Electrical supply	230/50/1
Current (A)	1.5
Power (W)	245
Refrigerant mass (g)	140
Refrigerant	R290

Dimensions

Height (mm)	2080
Width (mm)	1440
Depth (mm)	855
Gross volume (ltr)	1350
Net volume	959.8
GN size	2/1
Gross weight (kg)	221
Net weight (kg)	206

Build

Cabinet type	Glass
Finish ext/int	304 S/S & 304 S/S
Number of sections	2
Section configuration	Left hinge-Right hinge
System	Integral
Leg type	Legs

Energy

Climate Class	3
Energy grade	B
EEI	13.08
AEC (kWh)	1303.05
GWP	3
Min - max temperature (°C)	-1/5
Energy consumption (kWh/24hr)	3.57

Footnotes

- Supplied as standard with 80-110mm adjustable legs
- This glass door model operates in a maximum ambient temperature of 32°C
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.