

# **Product Code: FS90 27-108**

## Air cooled standard Ice Cuber



### Features & Benefits

#### FS90

- Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- Uses as little as 5 litres of water to produce 1 kilo of ice important where water is metered.
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Bin capacity: 42kgs
- Ice: Cubed 35x37x32mm

Base Fittings		Refrigeration		Electrical & Service Data	
Adjustable leg set	Option	Ice bin type	Integral	230/50/1	Standard
Product Extras		R134a - Industry Standard	Standard		Finish
Condensate some	Oution	Drain Rqd	20mm	Ctatalana ataul	Characterist of the charac
Condensate pump	Option	Specification		Stainless steel	Standard
		Air cooled ice maker	Standard		
		Width (mm)	700		
		Depth (mm)	580		
		Height (mm)	995		
		Cubes - 37 x 35 x 32mm	Standard		
		KG per 24 hours	82		

#### **Footnotes**

- Output figures quoted are based on 10°C water input and ambient air temp of 21°C
- Dimensions: Legs provided as standard to increase height for drainage where required 120cm maximum height increase
- Note: A minimum clearance of 15cm (6") must be left at the sides of the machine for routing cooling air drawn into and exhausted out of the compartment to maintain a proper condensing operation
- Maximum ambient air temperature 40°C; maximum input water temperature 35°C
- Everpure filter, cartridge and head kit available as an option
- Everpure water filter and ION clean installation kit available as an option



Energy



Quality



Value



Design



Hygiene



After Ca

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.