



The Refrigeration Experts

## Product specification

---



### FS20: 25kg Integral Ice Cuber

27-117

Air cooled ice cuber

#### **About the product**

Available to finance with our award-winning [interest-free credit](#) and [leasing](#)

Learn more about our [Drinks Service range](#)

## Why choose this product

- Innovatively designed with new user-friendly electro-mechanical controls to ensure reliability
- The models also incorporate a condenser thermostat, which ensures a full harvest of cubes
- Produces ultra cold square cubes that last longer in the glass, ice bucket and the machine's storage bin
- Uses as little as 5 litres of water to produce 1 kilo of ice - important where water is metered.
- The new flush system ensures clear ice free from impurities and eliminates the risk of lime-scale
- Bin capacity: 6.5 kgs
- Ice: Cubed 35x37x32mm

## Specification

Technical		Dimensions	
<b>Refrigerant</b>	R290	<b>Height (mm)</b>	600
<b>Electrical supply</b>	230/50/1	<b>Width (mm)</b>	340
<b>Fuse rating (A)</b>	10	<b>Depth (mm)</b>	480
<b>Current (A)</b>	2.3	<b>Net volume (ltr)</b>	6.5
<b>Power (W)</b>	653	<b>Bin Capacity (kg)</b>	6.5
<b>Refrigerant mass (g)</b>	80	<b>Leg type</b>	Feet
		<b>Gross weight (kg)</b>	33
		<b>Net weight (kg)</b>	29

Build		Energy	
<b>Finish ext/int</b>	S/S & S/S	<b>Climate Class</b>	5
<b>Section configuration</b>		<b>AEC (kWh)</b>	2135.25
<b>System</b>	Integral	<b>GWP</b>	3
		<b>Energy consumption (kWh/24hr)</b>	5.85

#### Footnotes

- A minimum clearance of 15cm (6") must be left at the sides of the machine for routing cooling air drawn into and exhausted out of the compartment to maintain a proper condensing operation
- Maximum ambient air temperature 40°C; maximum input water temperature 35°C

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.