

Product Code: LL2/1HD 14-101Low Level LL2/1HD Refrigerated Counter



Features & Benefits

- Ideal for quick service restaurants as it provides refrigerated storage at the cooking area
- Designed to carry up to 300kg (evenly spread) invaluable to any quick service cook off station
- Digital microprocessor controller and illuminated on/off switch
- Air distribution system ensures temperature is maintained throughout the counter
- Robust build with heavy duty handles and fixings to withstand constant usage
- Fitted with drawer locks and lockable castors
- Max pan depth is 100mm

Base Fittings		Doors		Refrigeration	
Castors 80mm	Standard	Solid	Standard	R134a - Industry Standard	Standard
Legs 100mm	Option	Specification	า	Integral Refrigeration System	Standard
Electrical & Service Data		Refrigerator +1/+4°C	Standard	Finish	
Connect Load	430	Width (mm)	1245	304 s/s	Standard
230/50/1	Standard	Depth (mm)	800	Worktop	Standard
Fuse Required (A)	10	Height (mm)	645		
Refrigerant Charge (kg)	0.180	Unpacked weight (Kgs)	90		
Energy		Packed weight (Kgs)	106.1		
AEC	763.872	Gross Volume (Ltr)	140		
Nett Volume	74.39718				
Energy Grade	С				
Global Warming Potential	1430				
Energy Efficiency Index	38.58				

Footnotes

• Decibel rating measured 1m high from the floor and 1m from the cabinet

Energy Performance Data and information



Foster Refrigerator- a division of ITW Ltd Oldmedow Road, KING'S LYNN, Norfolk PE30 4JU Tel: 0843 216 8800 Fax: 0843 216 4700 Registered in England No. 00559693 VAT No. 6B 792 4414 16



Application

This appliance is intended for use in ambient temperatures up to {1}°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit our policies







Quality



Value



Design



Hygiene



After Care

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.